


# 650V 50mΩ Silicon Carbide Power MOSFET

## Features

- AEC-Q101 qualified
- High blocking voltage with low on-resistance
- High switching speed with low capacitance
- Very fast and robust intrinsic body diode with low reverse recovery
- Very low switching losses
- Excellent avalanche ruggedness
- RoHS compliant



## Benefits

- Greater system efficiency
- Reduced cooling requirements
- Increased power density
- Increased system switching frequency
- Easy to parallel and simple to drive

Die Size(mm)
2.80*2.80 mm <sup>2</sup>

## Potential Applications

- Solar inverters
- Uninterrupted power supplies
- Switch mode power supplies
- Motor drives



## Description

The Sanan Semiconductor 650V/50mΩ silicon carbide power MOSFET uses advanced SiC MOSFET technology with low on-resistance, low switching losses, and a high operation temperature of 175°C. It is suitable for use in high frequency circuits and provides a reduction in overall system size, increased efficiency and increased switching frequency. It has been widely used in applications including solar inverters, uninterrupted power supplies, switch mode power supplies, and motor drives. Using RoHS compliant components and being AEC-Q101 qualified, it is qualified for use in industrial application.

## Product Specifications

Device	V <sub>DS</sub>	I <sub>D</sub> (25°C)	R <sub>(DS)on</sub>	Q <sub>rr</sub>
AMS0650050B	650V	45A	50mΩ	0.17µC

## CONTENTS

<b>Features .....</b>	<b>1</b>
<b>Benefits .....</b>	<b>1</b>
<b>Potential Applications .....</b>	<b>1</b>
<b>Description .....</b>	<b>1</b>
<b>Product Specifications .....</b>	<b>1</b>
<b>Table 1. Maximum Ratings .....</b>	<b>3</b>
<b>Table 2. Static Electrical Characteristics .....</b>	<b>4</b>
<b>Table 3. Dynamic Electrical Characteristics .....</b>	<b>4</b>
<b>Table 4. Reverse SiC Diode Characteristics .....</b>	<b>5</b>
<b>Electrical Characteristic Diagrams .....</b>	<b>6</b>
<b>Chip Dimensions .....</b>	<b>11</b>
<b>Ordering Information .....</b>	<b>11</b>
<b>Mechanical Parameters .....</b>	<b>12</b>
<b>Important Notices – Read Carefully .....</b>	<b>12</b>
<b>Warning .....</b>	<b>12</b>

**Table 1. Maximum Ratings**(T<sub>c</sub> = 25°C, unless otherwise specified)

Parameter	Symbol	Value	Unit	Test conditions
Drain-source voltage	V <sub>DSmax</sub>	650	V	V <sub>GS</sub> = 0V, I <sub>D</sub> = 100µA, T <sub>c</sub> = 25°C
Gate-source voltage, max. transient voltage	V <sub>GSmax</sub>	-10/+25		t <sub>p</sub> ≤ 0.5us, D < 1%, T <sub>c</sub> = 25°C
Gate-source voltage, max. static voltage	V <sub>GSmax</sub>	-8/+22		T <sub>c</sub> = 25°C
Gate-source voltage	V <sub>GSop</sub>	-5/+18		Recommended operation values, T <sub>c</sub> = 25°C
Continuous drain current	I <sub>D</sub>	45	A	V <sub>GS</sub> = 18V, T <sub>c</sub> = 25°C
		32		V <sub>GS</sub> = 18V, T <sub>c</sub> = 100°C
Pulsed drain current	I <sub>D(pulse)</sub>	111	A	Pulse width t <sub>p</sub> limited by T <sub>jmax</sub>
Operating junction temperature	T <sub>j</sub>	-55~175	°C	
Storage temperature	T <sub>stg</sub>	-55~175	°C	

**Table 2. Static Electrical Characteristics**(T<sub>j</sub> = 25°C, unless otherwise specified)

Parameter	Symbol	Values			Unit	Test conditions
		Min.	Typ.	Max.		
Drain-source breakdown voltage	V <sub>(BR)DSS</sub>	650	/	/		V <sub>GS</sub> = 0V, I <sub>D</sub> = 100μA
Gate threshold voltage	V <sub>GS(th)</sub>	1.8	2.8	4.2	V	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 6.5mA
		/	1.9	/		V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 6.5mA, T <sub>j</sub> = 175°C
Drain-source leakage current	I <sub>DSS</sub>	/	1	50	μA	V <sub>DS</sub> = 650V, V <sub>GS</sub> = 0V
Gate-source leakage current	I <sub>GSS</sub>	/	1	250	nA	V <sub>GS</sub> = 18V, V <sub>DS</sub> = 0V
Drain-source on-state resistance	R <sub>DS(on)</sub>	/	65	/	mΩ	V <sub>GS</sub> = 15V, I <sub>D</sub> = 20A
		/	50	65		V <sub>GS</sub> = 18V, I <sub>D</sub> = 20A
		/	62	/		V <sub>GS</sub> = 18V, I <sub>D</sub> = 20A, T <sub>j</sub> = 175°C
Transconductance	g <sub>fs</sub>	/	14	/	S	V <sub>DS</sub> = 20V, I <sub>D</sub> = 20A
		/	13	/		V <sub>DS</sub> = 20V, I <sub>D</sub> = 20A, T <sub>j</sub> = 175°C
Internal gate resistance	R <sub>g(int)</sub>	/	1.6	/	Ω	f = 1MHz, V <sub>AC</sub> = 25mV

**Table 3. Dynamic Electrical Characteristics**(T<sub>j</sub> = 25°C, unless otherwise specified)

Parameter	Symbol	Values			Unit	Test conditions
		Min.	Typ.	Max.		
Input capacitance	C <sub>iss</sub>	/	1415	/		
Output capacitance	C <sub>oss</sub>	/	135	/	pF	V <sub>GS</sub> = 0V, V <sub>DS</sub> = 600V, f = 1MHz, V <sub>AC</sub> = 25mV
Reverse transfer capacitance	C <sub>rss</sub>	/	2	/		
C <sub>oss</sub> stored energy	E <sub>oss</sub>	/	26	/	μJ	
Gate to source charge	Q <sub>gs</sub>	/	19	/	nC	V <sub>DD</sub> = 400V, V <sub>GS</sub> = -5/+18V, I <sub>D</sub> = 20A, I <sub>GS</sub> = 1mA
Gate to drain charge	Q <sub>gd</sub>	/	16	/		
Total gate charge	Q <sub>g</sub>	/	58	/		

**Table 4. Reverse SiC Diode Characteristics**(T<sub>j</sub> = 25°C, unless otherwise specified)

Parameter	Symbol	Values			Unit	Test conditions
		Min.	Typ.	Max.		
Diode forward voltage	V <sub>SD</sub>	/	4.2	/	V	V <sub>GS</sub> = -5V, I <sub>SD</sub> = 20A
		/	3.7	/		V <sub>GS</sub> = -5V, I <sub>SD</sub> = 20A, T <sub>j</sub> = 175°C
Continuous diode forward current	I <sub>S</sub>	/	/	45	A	V <sub>GS</sub> = -5V, T <sub>C</sub> = 25°C
Diode pulse current	I <sub>S, pulse</sub>	/	/	111	A	V <sub>GS</sub> = -5V, pulse width t <sub>p</sub> limited by T <sub>jmax</sub>
Reverse recovery time	t <sub>rr</sub>	/	15	/	ns	V <sub>GS</sub> = -5V, I <sub>SD</sub> = 20A, V <sub>R</sub> = 400V, dI/dt = 1.58kA/μs
Reverse recovery charge	Q <sub>rr</sub>	/	0.17	/	μC	
Peak reverse recovery current	I <sub>rrm</sub>	/	19	/	A	

**Electrical Characteristic Diagrams :** All the graphs are based on the TO-247-4L (which has higher thermal resistance than most packages used with topside sinter/solder)




Figure 1. Output characteristics at  $T_j = -55^\circ\text{C}$




Figure 2. Output characteristics at  $T_j = 25^\circ\text{C}$




Figure 3. Output characteristics at  $T_j = 175^\circ\text{C}$








Figure 4. Normalized on-resistance vs. temperature







 Figure 9. Body diode characteristic at  $T_j = 25^\circ\text{C}$ 

 Figure 10. Body diode characteristic at  $T_j = 175^\circ\text{C}$ 


Figure 11. Threshold voltage vs. temperature




Figure 12. Gate Charge Characteristic




Figure 13. 3rd quadrant characteristic  
at  $T_j = -55^\circ\text{C}$




Figure 14. 3rd quadrant characteristic  
at  $T_j = 25^\circ\text{C}$




Figure 15. 3rd quadrant characteristic  
at  $T_j = 175^\circ\text{C}$




Figure 16. Output capacitor stored energy




Figure 17. Capacitance vs. drain-source voltage  
(0 - 200V)




Figure 18. Capacitance vs. drain-source voltage  
(0 - 600V)




Figure 19. Reverse recovery charge vs.  $di_f/dt$





Figure 20. Reverse recovery current vs.  $di_f/dt$

## Chip Dimensions



Symbol	Dimensions	
	mm	inch
A	0.23	0.009
B	0.60	0.024
C	0.21	0.008
D	0.48	0.019
E	0.40	0.016
F	0.40	0.016
G	0.24	0.009
H	0.90	0.035
I	1.60	0.063
J	0.35	0.014
K	0.30	0.012
L	0.33	0.013
M	0.47	0.019
N	2.80	0.110
O	2.80	0.110

## Ordering Information

Part number	AMS0650050B
Package	Bare Die
Package Method	Wafer
RoHS	Yes

## Mechanical Parameters

Parameter	Type	Unit
Die Dimensions(L × W)	2.8*2.8	mm <sup>2</sup>
Exposed Source Pad Metal Dimensions(L × W) Each	0.9*1.6+0.6*0.4	mm <sup>2</sup>
Gate Pad Dimensions(L × W)	0.48*0.4	mm <sup>2</sup>
Die Thickness	150	µm
Top Side Source Metallization(Al)	4	µm
Top Side Gate Metallization(Al)	4	µm
Bottom Drain metallization(Ni / Ag)	0.4/1.2	µm

## Important Notices – Read Carefully

Before you use our products, you are requested to carefully read this document and fully understand its contents. Sanan Semiconductor Co., Ltd. shall not be in any way responsible or liable for failure, malfunction or accident arising from the use of Sanan's products.

Sanan Semiconductor Datasheets are subject to change. Information presented in this document is from the characterization of engineering lots. Sanan Semiconductor Co., Ltd reserves the right to change limits, test conditions, and dimensions without notice. Information contained in this document are typical values and shall in no event be regarded as a guarantee of characteristics. With respect to any information regarding the application of the product, Sanan hereby disclaims all warranties and liabilities of any kind. The information in this document is exclusively for trained technical staff. It is the responsibility of the customer's technical department to decide the suitability of the product in the customer's application and Sanan Semiconductor Co., Ltd assumes no responsibility or liability whatsoever for the use of the information contained in this document.

In case there is any clause in this document or in any other documents which is contradictory to this clause, this clause shall prevail. This clause shall survive after termination of this document.

## Warning

Due to technical requirements, Sanan's products may contain dangerous substances. For detailed information about the substance(s), please contact the Sanan office. Sanan Semiconductor Co., Ltd bears no responsibility for any damage whatsoever due to the substance(s) used in Sanan's products.

## Contact info

Website: <https://www.sanan-semiconductor.com/>  
<https://www.sanan-semiconductor.com/en>