



100V 1A Standard Rectifier – 1N4002

Rev 1.0
25/08/23

Standard recovery rectifier diode in bare die form

Features:

- Low leakage current
- High forward surge current capability
- Low forward voltage drop
- Robust construction
- High reliability tested grades.

Ordering Information

The following part suffixes apply:


- No suffix - MIL-STD-750 /2073 Visual Inspection
- "H" - MIL-STD-750 /2073 Visual Inspection
+ MIL-PRF-38534 Class H LAT
- "K" - MIL-STD-750 /2073 Visual Inspection
+ MIL-PRF-38534 Class K LAT

LAT = Lot Acceptance Test.


For further information on LAT process flows see below.

www.siliconsupplies.com/quality/bare-die-lot-qualification

Die Dimensions in μm (mils)



CHIP BACKSIDE IS CATHODE



Supply Formats:

- Default – Die in Waffle Pack (400 per tray capacity)
- Sawn Wafer on Tape – By specific request
- Unsawn Wafer – By specific request
- With additional electrical selection – By specific request

Mechanical Specification

Die Size (Unsawn)	1000 x 1000 39.37 x 39.37	μm mils
Anode Pad Size	450 x 450 17.72 x 17.72	μm mils
Die Thickness	220 (± 20) 8.66 (± 0.79)	μm mils
Top Metal Composition	Al 7.5 μm	
Back Metal Composition	Ti/Ni/Ag	





100V 1A Standard Rectifier – 1N4002

Rev 1.0
18/01/19

Absolute Maximum Ratings $T_J = 25^\circ\text{C}$ unless otherwise stated

PARAMETER	SYMBOL	VALUE	UNIT
Peak Repetitive Reverse Voltage	V_{RRM}	100	V
DC Blocking Voltage	V_R	100	V
RMS Reverse Voltage	$V_{R(RMS)}$	70	V
Average forward rectified current	$I_{F(AV)}, T_J = 75^\circ\text{C}$	1	A
Peak forward surge current ¹	I_{FSM}	30	A
Operating Junction temperature	T_J	-55 to 175	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-65 to 200	$^\circ\text{C}$

Electrical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise stated

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Maximum instantaneous Forward Voltage ²	V_F	$I_F = 1\text{A}$	-	-	1.1	V
Maximum Reverse Leakage Current	$I_{RM} @ V_{RRM}$	$V_{RRM} = 100\text{V}, T_J = 25^\circ\text{C}$	-	-	5	μA
		$V_{RRM} = 100\text{V}, T_J = 100^\circ\text{C}$	-	-	50	
Maximum Junction Capacitance	C_J	$V_R = 0, f = 1.0\text{MHz}$	-	-	40	pF

1. Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load
2. Pulse Width = 3.8ms

DISCLAIMER: The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Silicon Supplies Ltd hereby disclaims any and all warranties and liabilities of any kind.

LIFE SUPPORT POLICY: Silicon Supplies Ltd components may be used in life support devices or systems only with the express written approval of Silicon Supplies Ltd, if a failure of such components can reasonably be expected to cause the failure of that life support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

