



# 0.5W Zener Diode - 1N52\*B series


Rev 1.1  
05/04/19

Silicon Planar Zener diode in bare die form – 5% tolerance

## Features:

- Sharp Reverse Characteristics
- Low Reverse Current Levels
- High Reliability Gold Back Metal
- High Reliability tested grades.

## Die Dimensions in $\mu\text{m}$ (mils)



## Ordering Information

The following part suffixes apply:

- No suffix - Commercial grade die
- “H” – Hi-rel grade die + MIL-STD-38534 Class H LAT
- “K” – Hi-rel grade die + MIL-STD-38534 Class K LAT.

LAT = Lot acceptance Test.

For information on Hi-Rel LAT flows please see below.

[www.siliconsupplies.com/bare-die-lot-qualification](http://www.siliconsupplies.com/bare-die-lot-qualification)

## Supply Formats:

- Default – Die in Waffle Pack (400 per tray capacity)
- Sawn Wafer on Tape – By specific request
- Unsawn Wafer – By specific request
- With additional electrical selection – By specific request

## Mechanical Specification

|                        |                            |                       |
|------------------------|----------------------------|-----------------------|
| Die Size (Unsawn)      | 330 x 330<br>12.99 x 12.99 | $\mu\text{m}$<br>mils |
| Anode Pad Size         | 235 x 235<br>9.25 x 9.25   | $\mu\text{m}$<br>mils |
| Die Thickness          | 200<br>7.87                | $\mu\text{m}$<br>mils |
| Top Metal Composition  | Al                         |                       |
| Back Metal Composition | AuAs                       |                       |





# 0.5W Zener Diode - 1N52\*B series

Rev 1.1  
05/04/19

## Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise stated

| PARAMETER                              | SYMBOL    | VALUE       | UNIT             |
|--|-----------|-------------|------------------|
| Power Dissipation                      | $P_{TOT}$ | 500         | mW               |
| Junction Temperature                   | $T_J$     | 175         | $^\circ\text{C}$ |
| Storage Temperature Range              | $T_S$     | -65 to +200 | $^\circ\text{C}$ |
| Forward Voltage @ $I_F = 200\text{mA}$ | $V_F$     | 1.5         | V                |

## Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise stated

| DEVICE  | ZENER VOLTAGE RANGE |      |       | TEST CURRENT |           | REVERSE LEAKAGE CURRENT |     | DYNAMIC RESISTANCE |                    | TEMP. COEFFICIENT |
|---------|---------------------|------|-------|--------------|-----------|-------------------------|-----|--------------------|--------------------|-------------------|
|         | $V_Z @ I_{ZT1}$     |      |       | $I_{ZT2}$    | $I_{ZT2}$ | $I_R @ V_R$             |     | $Z_Z @ I_{ZT1}$    | $Z_{ZK} @ I_{ZT2}$ | $\alpha V_Z$      |
|         | V                   |      |       | mA           |           | $\mu\text{A}$           | V   | $\Omega$           |                    | %/K               |
|         | Min.                | Nom. | Max.  |              |           | Max.                    |     | Max.               | Max.               | Typ.              |
| 1N5221B | 2.28                | 2.4  | 2.52  | 20           | 0.25      | 100                     | 1   | 30                 | 1200               | -0.085            |
| 1N5222B | 2.38                | 2.5  | 2.63  | 20           | 0.25      | 100                     | 1   | 30                 | 1250               | -0.085            |
| 1N5223B | 2.57                | 2.7  | 2.84  | 20           | 0.25      | 75                      | 1   | 30                 | 1300               | -0.08             |
| 1N5224B | 2.66                | 2.8  | 2.94  | 20           | 0.25      | 75                      | 1   | 30                 | 1400               | -0.08             |
| 1N5225B | 2.85                | 3    | 3.15  | 20           | 0.25      | 50                      | 1   | 29                 | 1600               | -0.075            |
| 1N5226B | 3.14                | 3.3  | 3.47  | 20           | 0.25      | 25                      | 1   | 28                 | 1600               | -0.07             |
| 1N5227B | 3.42                | 3.6  | 3.78  | 20           | 0.25      | 15                      | 1   | 24                 | 1700               | -0.065            |
| 1N5228B | 3.71                | 3.9  | 4.10  | 20           | 0.25      | 10                      | 1   | 23                 | 1900               | -0.06             |
| 1N5229B | 4.09                | 4.3  | 4.52  | 20           | 0.25      | 5                       | 1   | 22                 | 2000               | 0.055             |
| 1N5230B | 4.47                | 4.7  | 4.94  | 20           | 0.25      | 5                       | 1   | 19                 | 1900               | 0.03              |
| 1N5231B | 4.85                | 5.1  | 5.36  | 20           | 0.25      | 5                       | 2   | 17                 | 1600               | 0.03              |
| 1N5232B | 5.32                | 5.6  | 5.88  | 20           | 0.25      | 5                       | 3   | 11                 | 1600               | 0.038             |
| 1N5233B | 5.70                | 6    | 6.30  | 20           | 0.25      | 5                       | 3.5 | 7                  | 1600               | 0.038             |
| 1N5234B | 5.89                | 6.2  | 6.51  | 20           | 0.25      | 5                       | 4.0 | 7                  | 1000               | 0.045             |
| 1N5235B | 6.46                | 6.8  | 7.14  | 20           | 0.25      | 3                       | 5.0 | 5                  | 750                | 0.05              |
| 1N5236B | 7.13                | 7.5  | 7.88  | 20           | 0.25      | 3                       | 6.0 | 6                  | 500                | 0.058             |
| 1N5237B | 7.79                | 8.2  | 8.61  | 20           | 0.25      | 3                       | 6.5 | 8                  | 500                | 0.062             |
| 1N5238B | 8.27                | 8.7  | 9.14  | 20           | 0.25      | 3                       | 6.5 | 8                  | 600                | 0.065             |
| 1N5239B | 8.65                | 9.1  | 9.56  | 20           | 0.25      | 3                       | 7.0 | 10                 | 600                | 0.068             |
| 1N5240B | 9.50                | 10   | 10.50 | 20           | 0.25      | 3                       | 8.0 | 17                 | 600                | 0.075             |
| 1N5241B | 10.45               | 11   | 11.55 | 20           | 0.25      | 2                       | 8.4 | 22                 | 600                | 0.076             |
| 1N5242B | 11.40               | 12   | 12.60 | 20           | 0.25      | 0.1                     | 9.1 | 30                 | 600                | 0.077             |
| 1N5243B | 12.35               | 13   | 13.65 | 9.5          | 0.25      | 0.1                     | 9.9 | 13                 | 600                | 0.079             |
| 1N5244B | 13.30               | 14   | 14.70 | 9.0          | 0.25      | 0.1                     | 10  | 15                 | 600                | 0.082             |





# 0.5W Zener Diode - 1N52\*B series

Rev 1.1  
05/04/19

## Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise stated

| DEVICE  | ZENER VOLTAGE RANGE |      |       | TEST CURRENT |           | REVERSE LEAKAGE CURRENT |    | DYNAMIC RESISTANCE |                    | TEMP. COEFFICIENT |
|---------|---------------------|------|-------|--------------|-----------|-------------------------|----|--------------------|--------------------|-------------------|
|         | $V_Z @ I_{ZT1}$     |      |       | $I_{ZT2}$    | $I_{ZT2}$ | $I_R @ V_R$             |    | $Z_Z @ I_{ZT1}$    | $Z_{ZK} @ I_{ZT2}$ | $\alpha V_Z$      |
|         | V                   |      |       | mA           |           | $\mu\text{A}$           | V  | $\Omega$           |                    | %/K               |
|         | Min.                | Nom. | Max.  |              |           | Max.                    |    | Max.               | Max.               | Typ.              |
| 1N5245B | 14.25               | 15   | 15.75 | 8.5          | 0.25      | 0.1                     | 11 | 19                 | 600                | 0.082             |
| 1N5246B | 15.20               | 16   | 16.80 | 7.8          | 0.25      | 0.1                     | 12 | 21                 | 600                | 0.083             |
| 1N5247B | 16.15               | 17   | 17.85 | 7.4          | 0.25      | 0.1                     | 13 | 23                 | 600                | 0.084             |
| 1N5248B | 17.1                | 18   | 18.90 | 7            | 0.25      | 0.1                     | 14 | 25                 | 600                | 0.085             |
| 1N5249B | 18.05               | 19   | 19.95 | 6.6          | 0.25      | 0.1                     | 14 | 29                 | 600                | 0.086             |
| 1N5250B | 19                  | 20   | 21.00 | 6.2          | 0.25      | 0.1                     | 15 | 33                 | 600                | 0.086             |
| 1N5251B | 20.9                | 22   | 23.10 | 5.6          | 0.25      | 0.1                     | 17 | 35                 | 600                | 0.087             |
| 1N5252B | 22.8                | 24   | 25.20 | 5.2          | 0.25      | 0.1                     | 18 | 41                 | 600                | 0.088             |
| 1N5253B | 23.75               | 25   | 26.25 | 5            | 0.25      | 0.1                     | 19 | 44                 | 600                | 0.089             |
| 1N5254B | 25.65               | 27   | 28.35 | 4.6          | 0.25      | 0.1                     | 21 | 49                 | 600                | 0.09              |
| 1N5255B | 26.6                | 28   | 29.40 | 4.5          | 0.25      | 0.1                     | 21 | 58                 | 600                | 0.091             |
| 1N5256B | 28.5                | 30   | 31.50 | 4.2          | 0.25      | 0.1                     | 23 | 70                 | 600                | 0.091             |
| 1N5257B | 31.35               | 33   | 34.65 | 3.8          | 0.25      | 0.1                     | 25 | 80                 | 700                | 0.092             |
| 1N5258B | 34.2                | 36   | 37.80 | 3.4          | 0.25      | 0.1                     | 27 | 93                 | 700                | 0.093             |
| 1N5259B | 37.05               | 39   | 40.95 | 3.2          | 0.25      | 0.1                     | 30 | 105                | 800                | 0.094             |
| 1N5260B | 40.85               | 43   | 45.15 | 3            | 0.25      | 0.1                     | 33 | 125                | 900                | 0.095             |
| 1N5261B | 44.65               | 47   | 49.35 | 2.7          | 0.25      | 0.1                     | 36 | 150                | 1000               | 0.095             |
| 1N5262B | 48.45               | 51   | 53.55 | 2.5          | 0.25      | 0.1                     | 39 | 170                | 1100               | 0.096             |
| 1N5263B | 53.2                | 56   | 58.80 | 2.2          | 0.25      | 0.1                     | 43 | 185                | 1300               | 0.096             |
| 1N5264B | 57                  | 60   | 63.00 | 2.1          | 0.25      | 0.1                     | 46 | 230                | 1400               | 0.097             |
| 1N5265B | 58.9                | 62   | 65.10 | 2            | 0.25      | 0.1                     | 47 | 270                | 1400               | 0.097             |
| 1N5266B | 64.6                | 68   | 71.40 | 1.8          | 0.25      | 0.1                     | 52 | 330                | 1600               | 0.097             |
| 1N5267B | 71.25               | 75   | 78.75 | 1.7          | 0.25      | 0.1                     | 56 | 370                | 1700               | 0.098             |


1. Operation above the absolute maximum rating may cause device failure. Operation at the absolute maximum ratings, for extended periods, may reduce device reliability.
2. Assembled in DO-35 package. Performance in die form subject to assembly heat sinking and die attach methods.





# 0.5W Zener Diode - 1N52\*B series

Rev 1.1  
05/04/19



Zener Impedance Versus Operating Current -  $Z_z$  Versus  $I_z$

**DISCLAIMER:** The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Silicon Supplies Ltd hereby disclaims any and all warranties and liabilities of any kind.

**LIFE SUPPORT POLICY:** Silicon Supplies Ltd components may be used in life support devices or systems only with the express written approval of Silicon Supplies Ltd, if a failure of such components can reasonably be expected to cause the failure of that life support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

