



# 0.5W Zener Diode - 1N5538B to 1N5546B


Rev 1.0  
05/04/19

Silicon Planar Zener diode in bare die form – 5% tolerance

## Features:

- Sharp Reverse Characteristics
- Low Reverse Current Levels
- High Reliability Gold Back Metal
- High Reliability Tested Grades.

## Die Dimensions in $\mu\text{m}$ (mils)



## Ordering Information

The following part suffixes apply:

- No suffix - Commercial grade die
- “H” – Hi-rel grade die + MIL-STD-38534 Class H LAT
- “K” – Hi-rel grade die + MIL-STD-38534 Class K LAT.

LAT = Lot acceptance Test.

For information on Hi-Rel LAT flows please see below.

[www.siliconsupplies.com/bare-die-lot-qualification](http://www.siliconsupplies.com/bare-die-lot-qualification)

## Supply Formats:

- Default – Die in Waffle Pack (400 per tray capacity)
- Sawn Wafer on Tape – By specific request
- Unsawn Wafer – By specific request
- With additional electrical selection – By specific request

## Mechanical Specification

Die Size (Unsawn)	330 x 330 12.99 x 12.99	$\mu\text{m}$ mils
Anode Pad Size	235 x 235 9.25 x 9.25	$\mu\text{m}$ mils
Die Thickness	200 7.87	$\mu\text{m}$ mils
Top Metal Composition	Al	
Back Metal Composition	AuAs	





# 0.5W Zener Diode - 1N5538B to 1N5546B

Rev 1.0  
05/04/19

## Absolute Maximum Ratings<sup>1</sup> $T_A = 25^\circ\text{C}$ unless otherwise stated

PARAMETER	SYMBOL	VALUE	UNIT
Power Dissipation <sup>2</sup>	$P_{TOT}$	500	mW
Junction Temperature	$T_J$	175	$^\circ\text{C}$
Storage Temperature Range	$T_S$	-65 to +175	$^\circ\text{C}$
Forward Voltage @ $I_F = 200\text{mA}$	$V_F$	1.1	V

## Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise stated

DEVICE	ZENER VOLTAGE RANGE	TEST CURRENT	REVERSE LEAKAGE CURRENT		ZENER <sup>3</sup> IMPEDANCE	ZENER REG <sup>4</sup>	LOW $V_Z$ CURRENT	MAX CURRENT	NOISE DENSITY
	$V_Z @ I_{ZT}$	$I_{ZT}$	$I_R @ V_R$		$Z_{ZT} @ I_{ZT}$	$\Delta V_Z$	$I_{ZL}$	$I_{ZM}$	$N_D @ 250\mu\text{A}$
	V	mA	$\mu\text{A}$	V	$\Omega$	V	mA	mA	$\mu\text{V}/\text{VHz}$
	Nom.		Max.	Max.	Typ.	Typ.			
1N5518B	3.3	20	5.0	1.0	26	0.90	2.0	115	0.5
1N5519B	3.6	20	3.0	1.0	24	0.90	2.0	105	0.5
1N5520B	3.9	20	1.0	1.0	22	0.85	2.0	98	0.5
1N5521B	4.3	20	3.0	1.5	18	0.75	2.0	88	0.5
1N5522B	4.7	10	2.0	2.0	22	0.60	1.0	81	0.5
1N5523B	5.1	5.0	2.0	2.5	26	0.65	0.25	75	0.5
1N5524B	5.6	3.0	2.0	3.5	30	0.30	0.25	68	1.0
1N5525B	6.2	1.0	1.0	5.0	30	0.20	0.01	61	1.0
1N5526B	6.8	1.0	1.0	6.2	30	0.10	0.01	56	1.0
1N5527B	7.5	1.0	0.5	6.8	35	0.05	0.01	51	2.0
1N5528B	8.2	1.0	0.5	7.5	40	0.05	0.01	46	4.0
1N5529B	9.1	1.0	0.1	8.2	45	0.05	0.01	42	4.0
1N5530B	10.0	1.0	0.05	9.1	60	0.10	0.01	38	4.0
1N5531B	11.0	1.0	0.05	9.9	80	0.20	0.01	35	5.0
1N5532B	12.0	1.0	0.05	10.8	90	0.20	0.01	32	10
1N5533B	13.0	1.0	0.01	11.7	90	0.20	0.01	29	15
1N5534B	14.0	1.0	0.01	12.6	100	0.20	0.01	27	20
1N5535B	15.0	1.0	0.01	13.5	100	0.20	0.01	25	20
1N5536B	16.0	1.0	0.01	14.4	100	0.20	0.01	24	20
1N5537B	17.0	1.0	0.01	15.3	100	0.20	0.01	22	20
1N5538B	18.0	1.0	0.01	16.2	100	0.20	0.01	21	20
1N5539B	19.0	1.0	0.01	17.1	100	0.20	0.01	20	20





# 0.5W Zener Diode - 1N5538B to 1N5546B

Rev 1.0  
05/04/19

## Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise stated

DEVICE	ZENER VOLTAGE RANGE <sup>3</sup>	TEST CURRENT	REVERSE LEAKAGE CURRENT		ZENER <sup>4</sup> IMPEDANCE	ZENER REG <sup>5</sup>	LOW $V_Z$ CURRENT	MAX CURRENT	NOISE DENSITY
	$V_Z @ I_{ZT}$	$I_{ZT}$	$I_R @ V_R$		$Z_{ZT} @ I_{ZT}$	$\Delta V_Z$	$I_{ZL}$	$I_{ZM}$	$N_D @ 250\mu\text{A}$
	V	mA	$\mu\text{A}$	V	$\Omega$	V	mA	mA	$\mu\text{V}/\text{VHz}$
	Nom.		Max.		Max.	Typ.	Typ.	Max.	Max.
1N5540B	20.0	1.0	0.01	18.0	100	0.20	0.01	19	20
1N5541B	22.0	1.0	0.01	19.8	100	0.25	0.01	17	20
1N5542B	24.0	1.0	0.01	21.6	100	0.30	0.01	16	20
1N5543B	25.0	1.0	0.01	22.4	100	0.35	0.01	15	20
1N5544B	28.0	1.0	0.01	25.2	100	0.40	0.01	14	20
1N5545B	30.0	1.0	0.01	27.0	100	0.45	0.01	13	20
1N5546B	33.0	1.0	0.01	29.7	100	0.50	0.01	12	20

1. Operation above the absolute maximum rating may cause device failure. Operation at the absolute maximum ratings, for extended periods, may reduce device reliability. 2. Assembled in DO-35 package. Performance in die form subject to assembly heat sinking and die attach methods. 3. No Suffix type numbers are  $\pm 20\%$  with guaranteed limits for only  $V_Z$ ,  $I_R$ , and  $V_F$ . Units with "A" suffix are  $\pm 10\%$  with guaranteed limits for  $V_Z$ ,  $I_R$ , and  $V_F$ . Units with guaranteed limits for all six parameters are indicated by a "B" suffix for  $+5.0\%$  units, "C" suffix for  $+2.0\%$  and "D" suffix for  $+1.0\%$  4. Zener impedance is derived by superimposing on  $I_{ZT}$  a 60Hz rms AC current equal to 10% of  $I_{ZT}$  5.  $\Delta V_Z$  is the maximum difference between  $V_Z @ I_{ZT}$  and  $V_Z @ I_{ZL}$  measured with the device junction in thermal equilibrium at an ambient temperature of  $+25^\circ \pm 3^\circ\text{C}$ .

**DISCLAIMER:** The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Silicon Supplies Ltd hereby disclaims any and all warranties and liabilities of any kind.

**LIFE SUPPORT POLICY:** Silicon Supplies Ltd components may be used in life support devices or systems only with the express written approval of Silicon Supplies Ltd, if a failure of such components can reasonably be expected to cause the failure of that life support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

