



# NPN Transistor Bare Die, 2N2368

Rev 1.0  
02/09/17

**Very High Speed Saturated Switch in bare die form**  
Complement PNP 2N4209 or 2N5771

## Features:

- Collector current up to 200mA
- Fast  $t_{on} + t_{off}$  switching times
- Characterized at temperature extremes
- High Reliability Gold Back Metal
- High Reliability tested grades for Military + Space

## Ordering Information:

The following part suffixes apply:


- No suffix - MIL-STD-750 /2072 Visual Inspection
- "H" - MIL-STD-750 /2072 Visual Inspection  
+ MIL-PRF-38534 Class H LAT
- "K" - MIL-STD-750 /2072 Visual Inspection  
+ MIL-PRF-38534 Class K LAT

LAT = Lot Acceptance Test.

For further information on LAT process flows see below.

[www.siliconsupplies.com/quality/bare-die-lot-qualification](http://www.siliconsupplies.com/quality/bare-die-lot-qualification)

## Die Dimensions in $\mu\text{m}$ (mils)



**E = EMITTER B = BASE**

**DIE BACK = COLLECTOR**

## Supply Formats:

- Default – Die in Waffle Pack (400 per tray capacity)
- Sawn Wafer on Tape – Specific request
- Unsawn Wafer – Specific request
- With additional electrical selection – Specific request
- Sawn as pairs or adjacent pair pick – Specific request

## Mechanical Specification

Die Size (Excluding Saw Street)	360 x 220 14.17 x 8.66	$\mu\text{m}$ mils
Base Pad Size Emitter Pad Size	75 x 95 2.95 x 3.74	$\mu\text{m}$ mils
Die Thickness	180 ( $\pm 20$ ) 7.09 ( $\pm 0.79$ )	$\mu\text{m}$ mils
Top Metal Composition	Al - 1.3 $\mu\text{m}$	
Back Metal Composition	AuAs - 0.9 $\mu\text{m}$	





# NPN Transistor Bare Die, 2N2368

Rev 1.0  
07/07/17

## Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise stated

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	$V_{CBO}$	40	V
Collector-Emitter Voltage	$V_{CEO}$	15	V
Emitter-Base Voltage	$V_{EBO}$	4.5	V
Collector Current	$I_C$	200	mA
Junction & Storage Temperature	$T_J, T_{stg}$	-55 to 150	$^\circ\text{C}$

## Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise stated

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
<b>OFF CHARACTERISTICS</b>						
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 10\mu\text{A}, I_E = 0$	40	-	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 10\text{mA}, I_B = 0$	15	-	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CES}$	$I_C = 10\mu\text{A}, V_{BE} = 0$	40	-	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 10\mu\text{A}, I_C = 0$	4.5	-	-	V
Collector Cut-off Current	$I_{CBO}$	$V_{CB} = 20\text{V}, I_E = 0$	-	-	400	nA
		$V_{CB} = 20\text{V}, I_E = 0, T_A = 125^\circ\text{C}^1$	-	-	30	$\mu\text{A}$
	$I_{CES}$	$V_{CB} = 20\text{V}$	-	-	400	nA
<b>ON CHARACTERISTICS</b>						
Forward-Current Transfer Ratio	$h_{FE}$	$V_{CE} = 1\text{V}, I_C = 10\text{mA}$	20	-	60	-
		$V_{CE} = 1\text{V}, I_C = 10\text{mA}, T_A = -55^\circ\text{C}^1$	10	-	-	-
		$V_{CE} = 2\text{V}, I_C = 100\text{mA}$	10	-	-	-
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 10\text{mA}, I_B = 1\text{mA}$	-	-	0.2	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = 10\text{mA}, I_B = 1\text{mA}$	0.7	-	0.85	V
<b>SMALL SIGNAL CHARACTERISTICS<sup>1</sup></b>						
Current Gain – Bandwidth Product	$f_T$	$I_C = 10\text{mA}, V_{CE} = 10\text{V}, f = 100\text{MHz}$	400	-	-	MHz
Output Capacitance	$C_{obo}$	$V_{CB} = 5\text{V}, I_E = 0, f = 1\text{MHz}$	-	-	4	pF
<b>SWITCHING CHARACTERISTICS<sup>1</sup></b>						
Turn-On Time	$t_{on}$	$V_{CC} = 3\text{V}, I_C = 10\text{mA}, I_{B1} = 3\text{mA}, I_{B2} = -1.5\text{mA}$	-	-	12	ns
Turn-Off Time	$t_{off}$	$V_{CC} = 3\text{V}, I_C = 10\text{mA}, I_{B1} = 3\text{mA}, I_{B2} = -1.5\text{mA}$	-	-	-	
Storage Time	$t_s$	$V_{CC} = 10\text{V}, I_{B1} = I_{B2} = I_C = 10\text{mA}$	-	-	10	

Note 1: Not production testing in die form, characterized by chip design and tested in package LAT





# NPN Transistor Bare Die, 2N2368

Rev 1.0  
07/07/17

## Typical Electrical Characteristics




Fig 1 - DC Current Gain versus Collector Current




Fig 2 - Collector-Emitter Saturation Voltage versus Collector Current




Fig 3 - Base-Emitter Saturation Voltage versus Collector Current




Fig 4 - Base-Emitter ON Voltage versus Collector Current




Fig 5 - Collector-Cut-off Current versus Ambient Temperature




Fig 6 - Output Capacitance versus Reverse Bias Voltage





# NPN Transistor Bare Die, 2N2368

Rev 1.0  
07/07/17

## Typical Electrical Characteristics (Continued)




Fig 7 - Switching Times versus Collector Current




Fig 8 - Switching Times versus Ambient Temperature




Fig 8 - Storage Time versus Turn On and Turn Off Base Currents




Fig 9 - Storage Time versus Turn On and Turn Off Base Currents




Fig 10 - Fall Time versus Turn On and Turn Off Base Currents




Fig 11 - Fall Time versus Turn On and Turn Off Base Currents







# NPN Transistor Bare Die, 2N2368

Rev 1.0  
07/07/17


## Typical Electrical Characteristics (Continued)



**Fig 12** - Fall Time versus Turn On and Turn Off Base Currents



**Fig 13** - Delay Time versus Base-Emitter Off Voltage and Turn On Base Current



**Fig 14** - Rise Time vs. Turn On Base Current and Collector Current

**DISCLAIMER:** The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Silicon Supplies Ltd hereby disclaims any and all warranties and liabilities of any kind.

**LIFE SUPPORT POLICY:** Silicon Supplies Ltd components may be used in life support devices or systems only with the express written approval of Silicon Supplies Ltd, if a failure of such components can reasonably be expected to cause the failure of that life support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

