



Bipolar TTL Logic – 7406

High Voltage Hex Inverter Buffer / Driver Logic IC in bare die form

Rev 1.1
31/08/21

Description

The 7406 comprises x6 inverter buffer/drivers with high voltage open-collector outputs. The device finds use as high-level circuit interface or for driving high-current loads and is also characterised to drive TTL inputs as inverted buffer. The device has a 30V minimum breakdown voltage and 40mA maximum sink current.

Features:

- High Sink-Current Capability: 40mA
- High Voltage Open-Collector Driver
- Minimum breakdown voltage: 30V
- Input Clamp Diodes minimize transmission-line effects
- TTL compatible inputs
- Direct drop-in replacement for obsolete components in long term programs.

Ordering Information


The following part suffixes apply:

- No suffix - MIL-STD-883 /2010B Visual Inspection

For High Reliability versions of this product please see

[5406](#)

Die Dimensions in μm (mils)



Supply Formats:

- Default – Die in Waffle Pack (400 per tray capacity)
- Sawn Wafer on Tape – On request
- Unsawn Wafer – On request
- Die Thickness \leftrightarrow 350 μm (14 Mils) – On request
- Assembled into Ceramic Package – On request

Mechanical Specification

Die Size (Unsawn)	1450 x 1400 57 x 55	μm mils
Minimum Bond Pad Size	140 x 140 5.5 x 5.5	μm mils
Die Thickness	350 (\pm 20) 13.78 (\pm 0.79)	μm mils
Top Metal Composition	Al 1%Si 1.1 μm	
Back Metal Composition	N/A – Bare Si	






Bipolar TTL Logic – 7406

Rev 1.1
31/08/21


Pad Layout and Functions



PAD	FUNCTION	COORDINATES (mm)	
		X	Y
1	1A	0.090	0.380
2	1Y	0.090	0.090
3	2A	0.460	0.090
4	2Y	0.830	0.090
5	3A	1.220	0.090
6	3Y	1.220	0.380
7	GND	1.220	0.630
8	4Y	1.220	0.880
9	4A	1.220	1.170
10	5Y	0.830	1.170
11	5A	0.460	1.170
12	6Y	0.090	1.170
13	6A	0.090	0.880
14	V _{CC}	0.090	0.630

CONNECT CHIP BACK TO GND OR FLOAT

Logic Diagram



Truth Table

INPUTS	OUTPUT
A	Y
L	Z
H	L

H = High level (steady state)
L = Low level (steady state)
Z = High Impedance





Absolute Maximum Ratings¹

PARAMETER	SYMBOL	VALUE	UNIT
DC Supply Voltage	V_{CC}	7.0	V
DC Input Voltage	V_{IN}	5.5	V
DC Output Voltage	V_{OUT}	30	
Storage Temperature Range	T_{STG}	-65 to 150	°C

1. Operation above the absolute maximum rating may cause device failure. Operation at the absolute maximum ratings, for extended periods, may reduce device reliability.

Recommended Operating Conditions

PARAMETER	SYMBOL	MIN	MAX	UNITS
Supply Voltage	V_{CC}	4.75	5.25	V
High-Level Input Voltage	V_{IH}	2	-	V
Low-Level Input Voltage	V_{IL}	-	0.8	V
High-Level Output Voltage	V_{OH}	-	30	V
Low-Level Output Current	I_{OL}	-	40	mA
Operating Temperature Range	T_J	-40	+85	°C

DC Electrical Characteristics² $T_J = -40^{\circ}\text{C}$ to 85°C unless otherwise specified

PARAMETER	SYMBOL	CONDITIONS	LIMITS			UNITS
			MIN	TYP	MAX	
Input Clamp Voltage	V_{IK}	$V_{CC} = 4.75\text{V}, I_{IN} = -12\text{mA}$	-	-	-1.5	V
High-Level Output Current	I_{OH}	$V_{CC} = 4.27\text{V}, V_{IL} = 0.8\text{V}, V_{OH} = 30\text{V}$	-	-	0.25	mA
Low-Level Output Voltage	V_{OL}	$V_{CC} = 4.75\text{V}, V_{IH} = 2\text{V}, I_{OL} = 16\text{mA}$	-	-	0.4	V
		$V_{CC} = 4.75\text{V}, V_{IH} = 2\text{V}, I_{OL} = 40\text{mA}$	-	-	0.7	
Input Current	I_{IN}	$V_{CC} = 5.25\text{V}, V_{IN} = 5.25\text{V}$	-	-	1	mA
High-Level Input Current	I_{IH}	$V_{CC} = 5.25\text{V}, V_{IH} = 2.4\text{V}$	-	-	0.04	mA
Low-Level Input Current	I_{IL}	$V_{CC} = 5.25\text{V}, V_{IL} = 0.4\text{V}$	-	-	-1.6	mA
Supply Current	I_{CC}	$V_{CC} = 5.25, \text{Output High}$	-	-	48	mA
		$V_{CC} = 5.25, \text{Output Low}$	-	-	51	





Bipolar TTL Logic – 7406


Rev 1.1
31/08/21

AC Electrical Characteristics²


PARAMETER	SYMBOL	CONDITIONS	LIMITS			UNITS
			MIN	TYP	MAX	
Turn-Off Delay, Input to Output	t_{PLH}	$T_A = 25^\circ\text{C}$, $V_{CC} = 5\text{V}$, $R_L = 110\Omega$, $C_L = 15\text{pF}$, Input $t_r = t_f = 10\text{ns}$	-	-	18	ns
Turn-On Delay, Input to Output	t_{PHL}		-	-	28	

2. Not production tested in die form, characterized by chip design

Switching Waveform



Test Circuit



* Includes all probe and jig capacitance

DISCLAIMER: The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Silicon Supplies Ltd hereby disclaims any and all warranties and liabilities of any kind.

LIFE SUPPORT POLICY: Silicon Supplies Ltd components may be used in life support devices or systems only with the express written approval of Silicon Supplies Ltd, if a failure of such components can reasonably be expected to cause the failure of that life support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

