



250V 0.4A Fast Switching Diode – BAS21



Rev 1.0
27/9/20

Small-Signal high voltage switching diode in bare die form

Features:

- Fast Switching Speed
- High conductance
- High minimum breakdown voltage 275V
- General purpose switching applications
- High reliability tested grades.

Die Dimensions in μm (mils)



CHIP BACKSIDE IS CATHODE

Ordering Information

The following part suffixes apply:

- No suffix - MIL-STD-750 /2073 Visual Inspection
- "H" - MIL-STD-750 /2073 Visual Inspection
+ MIL-PRF-38534 Class H LAT
- "K" - MIL-STD-750 /2073 Visual Inspection
+ MIL-PRF-38534 Class K LAT

LAT = Lot Acceptance Test.

For further information on LAT process flows see below.

www.siliconsupplies.com/quality/bare-die-lot-qualification

Supply Formats:

- Default – Die in Waffle Pack (400 per tray capacity)
- Sawn Wafer on Tape – By specific request
- Unsawn Wafer – By specific request
- Die Thickness \leftrightarrow 180 μm (7 Mils) – On request
- With additional electrical selection – On request

Mechanical Specification

Die Size (Unsawn)	410 x 410 16.14 x 16.14	μm mils
Anode Pad Size	200 X 200 7.87 X 7.87	μm mils
Die Thickness	180 (\pm 15) 7.09 (\pm 0.59)	μm mils
Top Metal Composition	Al	
Back Metal Composition	AuAs	





250V 0.4A Fast Switching Diode – BAS21

Rev 1.0
27/9/20

Absolute Maximum Ratings¹ $T_J = 25^\circ\text{C}$ unless otherwise stated

PARAMETER	SYMBOL	VALUE	UNIT
Non-repetitive Peak Reverse Voltage	V_{RSM}	300	V
Repetitive Peak Reverse Voltage	V_{RRM}	275	V
Working Peak Reverse Voltage	V_{RWM}	250	V
Average Rectified Output Current	I_O	200	mA
DC Forward Current	I_F	400	mA
Recurrent Peak Forward Current	I_f	625	mA
Non-repetitive Peak forward surge current	I_{FSM}	Pulse width 1s	1
		Pulse width 1 μ s	4
Power Dissipation	P_D	250	mW
Operating Junction temperature	T_J	-55 to 175	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-65 to 200	$^\circ\text{C}$

1. Operation above the absolute maximum rating may cause device failure. Operation at the absolute maximum ratings, for extended periods, may reduce device reliability.

Electrical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise stated

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
Breakdown Voltage	V_R	$I_R = 100\mu\text{A}$	275	-	-	V
Forward Voltage ²	V_F	$I_F = 100\text{mA}$	-	-	1.00	V
		$I_F = 200\text{mA}$	-	-	1.25	
Reverse Leakage	I_R	$V_R = 200\text{V}$	-	-	0.10	μA
		$V_R = 200\text{V}, T_J = 150^\circ\text{C}$	-	-	100	
Total Capacitance	C_T	$V_R = 0\text{V}, f = 1\text{MHz}$	-	-	5	pF
Reverse Recovery Time	t_{rr}	$I_F = I_R = 30\text{mA}, I_{rr} = 3\text{mA}, R_L = 100\Omega$	-	-	50	ns

2. Pulse Width = 8.3ms, Non-recurrent square wave





250V 0.4A Fast Switching Diode – BAS21

Rev 1.0
27/9/20

Typical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise stated




FIGURE 1. Forward Voltage Characteristics




FIGURE 2. Reverse Current Characteristics

DISCLAIMER: The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Silicon Supplies Ltd hereby disclaims any and all warranties and liabilities of any kind.

LIFE SUPPORT POLICY: Silicon Supplies Ltd components may be used in life support devices or systems only with the express written approval of Silicon Supplies Ltd, if a failure of such components can reasonably be expected to cause the failure of that life support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

