



4.5 GHz Wideband PNP Chip – BFT92

Silicon PNP Planar RF Transistor in bare die form

**Rev 1.2
23/11/17**

Description

PNP transistor in unencapsulated chip form. It is primarily intended for use in RF wideband amplifiers, such as in aerial amplifiers, radar systems, oscilloscopes, spectrum analyzers, etc. The transistor features low intermodulation distortion and high power gain; due to its very high transition frequency, it also has excellent wideband properties and low noise up to high frequencies. NPN complements are BFR92 and BFR92A.

Ordering Information

The following part suffixes apply:

- No suffix - MIL-STD-883 /2010B Visual Inspection
- “H” - MIL-STD-883 /2010B Visual Inspection
+ MIL-STD-38534 Class H LAT
- “K” - MIL-STD-883 /2010A Visual Inspection (Space)
+ MIL-STD-38534 Class K LAT

LAT = Lot Acceptance Test.


For more information on Hi-Rel LAT flows please see below.

www.siliconsupplies.com/bare_die_lot_qualification

Features:

- High Power Gain
- Low Noise
- Wide Transition Frequency

Die Dimensions in μm (mils)



CHIP BACK IS COLLECTOR

Supply Formats:

- Default – Die in Waffle Pack (400 per tray capacity)
- Sawn Wafer on Tape – By specific request
- Unsawn Wafer – By specific request
- With additional electrical selection – Specific request
- Sawn as pairs or adjacent pair pick – Specific request

Mechanical Specification

Die Size (Unsawn)	380 x 380 14.96 x 14.96	μm mils
Minimum Bond Pad Size	100 x 75 3.94 x 2.95	μm mils
Die Thickness	280 (± 10) 11 (± 0.4)	μm mils
Top Metal Composition	Au	
Back Metal Composition	Au	





4.5 GHz Wideband PNP Chip – BFT92

Silicon PNP Planar RF Transistor in bare die form

Rev 1.2
3/11/17

Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
V_{CBO}	collector-base voltage	open emitter	-	-20	V
V_{CEO}	collector-emitter voltage	open base	-	-15	V
V_{EBO}	emitter-base voltage	open collector	-	-2	V
I_C	DC collector current	-	-	-25	mA
P_{tot}	total power dissipation	-	-	200	mW
T_{stg}	storage temperature	-	-65	150	$^\circ\text{C}$
T_J	junction temperature	-	-	175	$^\circ\text{C}$

Electrical Characteristics $T_A = 25^\circ\text{C}$

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
I_{CBO}	collector cut-off current	$I_E = 0$; $V_{CB} = -10\text{V}$	-	-	-100	nA
h_{FE}	DC current gain	$I_C = -14\text{mA}$; $V_{CE} = -10\text{V}$	20	-	-	
f_T	transition frequency	$I_C = -14\text{mA}$; $V_{CE} = -10\text{V}$ $f = 300\text{ MHz}$	-	4.5	-	GHz
G_P	power gain	$I_C = -14\text{mA}$; $V_{CE} = -10\text{V}$ $f = 500\text{ MHz}$	-	16	-	dB
NF	noise figure	$I_C = -2\text{mA}$; $V_{CE} = -10\text{V}$; $f = 500\text{ MHz}$	-	2.4	-	dB

DISCLAIMER: The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Silicon Supplies Ltd hereby disclaims any and all warranties and liabilities of any kind.

LIFE SUPPORT POLICY: Silicon Supplies Ltd components may be used in life support devices or systems only with the express written approval of Silicon Supplies Ltd, if a failure of such components can reasonably be expected to cause the failure of that life support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

