



0.5W Zener Diode - BZX55A* series

Rev 1.0

0.5W 5mA I_{ZT} Silicon Planar Zener diode in bare die form – 1% tolerance, “A” grade 07/04/19

Features:

- Tight tolerance reverse breakdown voltage
- Larger die size for dissipation
- I_R characterized at 125°C
- Sharp reverse characteristics & low reverse current
- High reliability gold back metal

Ordering Information

The following part suffixes apply:


- No suffix - MIL-STD-750 /2073 Visual Inspection
- “H” - MIL-STD-750 /2073 Visual Inspection
+ MIL-PRF-38534 Class H LAT
- “K” - MIL-STD-750 /2072 Visual Inspection
+ MIL-PRF-38534 Class K LAT

LAT = Lot Acceptance Test.

For further information on LAT process flows see below.

www.siliconsupplies.com/quality/bare-die-lot-qualification

Die Dimensions in µm (mils)



CHIP BACKSIDE IS CATHODE

Supply Formats:

- Default – Die in Waffle Pack (400 per tray capacity)
- Sawn Wafer on Tape – By specific request
- Unsawn Wafer – By specific request
- Lower precision V_Z tolerances:
2% - B grade, 5% - C grade

Mechanical Specification

Die Size (Unsawn)	450 x 450 17.72 x 17.72	µm mils
Anode Pad Size	235 x 235 9.25 x 9.25	µm mils
Die Thickness	200 7.87	µm mils
Top Metal Composition	Al	
Back Metal Composition	Au	





0.5W Zener Diode - BZX55A* series

Rev 1.0
07/04/19

Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise stated

PARAMETER	SYMBOL	VALUE	UNIT
Power Dissipation	P_{TOT}	500	mW
Junction Temperature	T_J	200	$^\circ\text{C}$
Storage Temperature Range	T_S	-65 to +200	$^\circ\text{C}$
Forward Voltage @ $I_F = 100\text{mA}$	V_F	1.3	V

Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise stated

DEVICE	ZENER VOLTAGE RANGE			TEST CURRENT		REVERSE LEAKAGE CURRENT			DYNAMIC RESISTANCE	
	$V_Z @ I_{ZT1}$			I_{ZT1}	I_{ZT2}	$I_R @ V_R$			$Z_Z @ I_{ZT1}$	$Z_{ZK} @ I_{ZT2}$
	V			mA		$T_A = 25^\circ\text{C}$	$T_A = 125^\circ\text{C}$		f = 1 kHz	
	Min.	Nom.	Max.			$\mu\text{A Max.}$		V	Max.	Max.
BZX55A10	9.90	10	10.10	5	1	0.1	2.0	7.5	15	70
BZX55A11	10.89	11	11.11	5	1	0.1	2.0	8.2	20	70
BZX55A12	11.88	12	12.12	5	1	0.1	2.0	9.1	20	90
BZX55A13	12.87	13	13.13	5	1	0.1	2.0	10	26	110
BZX55A15	14.85	15	15.15	5	1	0.1	2.0	11	30	110
BZX55A16	15.84	16	16.16	5	1	0.1	2.0	12	40	170
BZX55A18	17.82	18	18.18	5	1	0.1	2.0	13	50	170
BZX55A20	19.80	20	20.20	5	1	0.1	2.0	15	55	220
BZX55A22	21.78	22	22.22	5	1	0.1	2.0	16	55	220
BZX55A24	23.76	24	24.24	5	1	0.1	2.0	18	80	220
BZX55A27	26.73	27	27.27	5	1	0.1	2.0	20	80	220
BZX55A30	29.70	30	30.30	5	1	0.1	2.0	22	80	220
BZX55A33	32.67	33	33.33	5	1	0.1	2.0	24	80	220
BZX55A36	35.64	36	36.36	5	1	0.1	2.0	27	80	220

1. Operation above the absolute maximum rating may cause device failure. Operation at the absolute maximum ratings, for extended periods, may reduce device reliability.
2. Assembled in DO-35 package. Performance in die form subject to assembly heat sinking and die attach methods.

Zener Voltages 2.4V to 9.1V are constructed using a smaller die geometry.

Please see [here](#) for further details






0.5W Zener Diode - BZX55A* series

Rev 1.0
07/04/19

Typical Electrical Characteristics



Zener Impedance Versus Operating Current - Z_Z Versus I_Z

DISCLAIMER: The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Silicon Supplies Ltd hereby disclaims any and all warranties and liabilities of any kind.

LIFE SUPPORT POLICY: Silicon Supplies Ltd components may be used in life support devices or systems only with the express written approval of Silicon Supplies Ltd, if a failure of such components can reasonably be expected to cause the failure of that life support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

