



0.5W, 5mA I_{ZT} , Bare Die Zener Diode

Rev 1.0
07/07/17

Silicon Planar Zener diode in bare die form – 5% tolerance

Features:

- I_R Characterized @ 125°C
- Sharp Reverse Characteristics
- Low Reverse Current Levels
- High Reliability Gold Back Metal
- High Reliability tested grades.

Ordering Information

The following part suffixes apply:


- No suffix - MIL-STD-750 /2073 Visual Inspection
- “H” - MIL-STD-750 /2073 Visual Inspection
+ MIL-PRF-38534 Class H LAT
- “K” - MIL-STD-750 /2072 Visual Inspection
+ MIL-PRF-38534 Class K LAT

LAT = Lot Acceptance Test.

For further information on LAT process flows see below.

www.siliconsupplies.com/quality/bare-die-lot-qualification

Die Dimensions in μm (mils)



Supply Formats:

- Default – Die in Waffle Pack (400 per tray capacity)
- Sawn Wafer on Tape – By specific request
- Unsawn Wafer – By specific request
- With additional electrical selection – By specific request

Mechanical Specification

Die Size (Unsawn)	450 x 450 17.72 x 17.72	μm mils
Anode Pad Size	235 x 235 9.25 x 9.25	μm mils
Die Thickness	200 7.87	μm mils
Top Metal Composition	Al	
Back Metal Composition	Au	





0.5W, 5mA I_{ZT} , Bare Die Zener Diode

Rev 1.0
07/07/17

Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise stated

PARAMETER	SYMBOL	VALUE	UNIT
Power Dissipation	P _{TOT}	500	mW
Junction Temperature	T _J	200	°C
Storage Temperature Range	T _S	-65 to +200	°C
Forward Voltage @ I _F = 100mA	V _F	1.3	V

Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise stated

DEVICE	ZENER VOLTAGE RANGE			TEST CURRENT		REVERSE LEAKAGE CURRENT			DYNAMIC RESISTANCE	
	V _Z @ I _{ZT1}			I _{ZT1}	I _{ZT2}	I _R @ V _R			Z _Z @ I _{ZT1}	Z _{ZK} @ I _{ZT2}
	V			mA		μA Max.		V	Ω	
	Min.	Nom.	Max.						Max.	Max.
BZX55C10	9.4	10	10.6	5	1	0.1	2.0	7.5	15	70
BZX55C11	10.4	11	11.6	5	1	0.1	2.0	8.2	20	70
BZX55C12	11.4	12	12.7	5	1	0.1	2.0	9.1	20	90
BZX55C13	12.4	13	14.1	5	1	0.1	2.0	10	26	110
BZX55C15	13.8	15	15.6	5	1	0.1	2.0	11	30	110
BZX55C16	15.3	16	17.1	5	1	0.1	2.0	12	40	170
BZX55C18	16.8	18	19.1	5	1	0.1	2.0	13	50	170
BZX55C20	18.8	20	21.2	5	1	0.1	2.0	15	55	220
BZX55C22	20.8	22	23.3	5	1	0.1	2.0	16	55	220
BZX55C24	22.8	24	25.6	5	1	0.1	2.0	18	80	220
BZX55C27	25.1	27	28.9	5	1	0.1	2.0	20	80	220
BZX55C30	28	30	32	5	1	0.1	2.0	22	80	220
BZX55C33	31	33	35	5	1	0.1	2.0	24	80	220
BZX55C36	34	36	38	5	1	0.1	2.0	27	80	220

Zener Voltages 2.4V to 9.1V are constructed using a smaller die geometry.

Please see [here](#) for further details





0.5W, 5mA I_{ZT} , Bare Die Zener Diode

Rev 1.0
07/07/17

Typical Electrical Characteristics



Zener Impedance Versus Operating Current - Z_Z Versus I_Z

DISCLAIMER: The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Silicon Supplies Ltd hereby disclaims any and all warranties and liabilities of any kind.

LIFE SUPPORT POLICY: Silicon Supplies Ltd components may be used in life support devices or systems only with the express written approval of Silicon Supplies Ltd, if a failure of such components can reasonably be expected to cause the failure of that life support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

