



600 Watt, Uni-Directional TVS Diode



Rev 1.0
12/04/18

Silicon Transient Voltage Suppressor diode in bare die form

Features:

- 600W peak pulse power dissipation
- Excellent clamping capabilities
- Low Leakage Current
- Metalized for Wire Bonding
- High Reliability tested grades.

Die Dimensions in μm (mils)



Ordering Information

The following part suffixes apply:

- No suffix - MIL-STD-750 /2073 Visual Inspection
- "H" - MIL-STD-750 /2073 Visual Inspection
+ MIL-PRF-38534 Class H LAT
- "K" - MIL-STD-750 /2072 Visual Inspection
+ MIL-PRF-38534 Class K LAT

LAT = Lot Acceptance Test.

For further information on LAT process flows see below.

www.siliconsupplies.com/quality/bare-die-lot-qualification

Supply Formats:

- Default – Die in Waffle Pack (100 per tray capacity)
- Sawn Wafer on Tape – By specific request
- Unsawn Wafer – By specific request
- With additional electrical selection – By specific request

Mechanical Specification

Die Size (Unsawn)	1730 x 1730 68.11 x 68.11	μm mils
Anode Pad Size	1480 x 1380 65 x 65	μm mils
Die Thickness	250 9.84	μm mils
Top Metal Composition	Al $\geq 4\mu\text{m}$	
Back Metal Composition	Ti/Ni/Ag $\geq 2.5\mu\text{m}$	





600 Watt, Uni-Directional TVS Diode

Rev 1.0
12/04/18

Absolute Maximum Ratings $T_J = 25^\circ\text{C}$ unless otherwise stated

PARAMETER	SYMBOL	VALUE	UNIT
Peak power dissipation 10/1000 μs waveform ¹	P_{PP}	600	W
Peak forward surge current, 8.3ms single half sine-wave ²	I_{FSM}	100	A
ESD IEC61000-4-2 (Air) ³	V_{ESD}	$\pm 30\text{V}$	kV
ESD IEC61000-4-2 (Contact) ³			
Operating Temperature Range	T_J	-55 to +175	$^\circ\text{C}$
Storage Temperature Range	T_S	-65 to +200	$^\circ\text{C}$

1. Performance at die level dependent on assembly method and substrate choice. 2. Measured on 8.3 ms single half sine-wave or equivalent square wave, duty cycle = 4 pulses per minute maximum. 3. Tested in SMAF package.

Electrical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise stated

DEVICE ⁴	REVERSE STAND-OFF VOLTAGE	BREAKDOWN VOLTAGE @ I_T		TEST CURRENT	MAX CLAMPING VOLTAGE $V_C @ I_{PP}$	PEAK PULSE CURRENT	REVERSE LEAKAGE $I_R @ V_{RRM}$
	V_{RRM}	$V_{BR(MIN)}$ (V)	$V_{BR(MAX)}$ (V)	I_T	V_C	I_{PP}	I_R
	V	V	V	mA	V	A	μA
P6SE3.3A	3.3	5.23	5.97	10	8	75	50
P6SE5.0A	5	6.43	6.97	10	9.2	65.2	20
P6SE6.0A	6	6.7	7.34	10	10.3	58.3	20
P6SE6.5A	6.5	7.25	7.95	10	11.2	53.6	15
P6SE7.0A	7	7.81	8.57	10	12	50	15
P6SE7.5A	7.5	8.36	9.18	1	12.9	46.5	10
P6SE8.0A	8	8.92	9.8	1	13.6	44.1	2
P6SE8.5A	8.5	9.47	10.37	1	14.4	41.7	2
P6SE9.0A	9	10.03	11.07	1	15.4	39	0.2
P6SE10A	10	11.13	12.27	1	17	35.3	0.2
P6SE11A	11	12.23	13.47	1	18.2	33	0.2
P6SE12A	12	13.33	14.67	1	19.9	30.2	0.2
P6SE13A	13	14.43	15.87	1	21.5	27.9	0.8
P6SE14A	14	15.63	17.17	1	23.2	25.9	0.8
P6SE15A	15	16.73	18.29	1	24.4	24.6	0.8
P6SE16A	16	17.83	19.67	1	26	23.1	0.8
P6SE17A	17	18.93	20.87	1	27.6	21.7	0.8
P6SE18A	18	20.03	22.07	1	29.2	20.5	0.8
P6SE20A	20	22.23	24.47	1	32.4	18.5	0.8
P6SE22A	22	24.43	26.87	1	35.5	16.9	0.8





600 Watt, Uni-Directional TVS Diode

Rev 1.0
12/04/18

Electrical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise stated

DEVICE ⁴	REVERSE STAND-OFF VOLTAGE	BREAKDOWN VOLTAGE @ I_T		TEST CURRENT	MAX CLAMPING VOLTAGE $V_C @ I_{PP}$	PEAK PULSE CURRENT	REVERSE LEAKAGE $I_R @ V_{RRM}$
	V_{RRM}	$V_{BR(MIN)}$ (V)	$V_{BR(MAX)}$ (V)	I_T	V_C	I_{PP}	I_R
	V	V	V	mA	V	A	μA
P6SE24A	24	26.73	29.47	1	38.9	15.4	0.8
P6SE26A	26	28.93	31.87	1	42.1	14.2	0.8
P6SE28A	28	31.13	34.37	1	45.4	13.2	0.8
P6SE30A	30	33.33	36.77	1	48.4	12.4	0.8
P6SE33A	33	36.73	40.57	1	53.3	11.3	0.8
P6SE36A	36	40.03	44.17	1	58.1	10.3	0.8
P6SE40A	40	44.43	49.07	1	64.5	9.3	0.8
P6SE43A	43	47.83	52.77	1	69.4	8.6	0.8
P6SE45A	45	50.03	55.27	1	72.7	8.3	0.8
P6SE48A	48	53.33	58.87	1	77.4	7.7	0.8
P6SE51A	51	56.73	62.67	1	82.4	7.3	0.8
P6SE54A	54	60.03	66.27	1	87.1	6.9	0.8
P6SE58A	58	64.43	71.17	1	93.6	6.4	0.8
P6SE60A	60	66.73	73.67	1	96.8	6.2	0.8
P6SE64A	64	71.13	78.57	1	103	5.8	0.8

4. Suffix "A" denotes 5% tolerance of V_{BR}

DISCLAIMER: The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Silicon Supplies Ltd hereby disclaims any and all warranties and liabilities of any kind.

LIFE SUPPORT POLICY: Silicon Supplies Ltd components may be used in life support devices or systems only with the express written approval of Silicon Supplies Ltd, if a failure of such components can reasonably be expected to cause the failure of that life support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

