



# 200 Watt, Uni-Directional TVS Diode



Rev 1.0  
02/12/24

Silicon Transient Voltage Suppressor diode in bare die form

## Features:

- 200W peak pulse power dissipation
- Excellent clamping capabilities
- Very fast response time
- Metalized for Wire Bonding
- High Reliability tested grades.

## Die Dimensions in $\mu\text{m}$ (mils)



## Ordering Information

The following part suffixes apply:

- No suffix - MIL-STD-750 /2073 Visual Inspection
- "H" - MIL-STD-750 /2073 Visual Inspection  
+ MIL-PRF-38534 Class H LAT
- "K" - MIL-STD-750 /2072 Visual Inspection  
+ MIL-PRF-38534 Class K LAT

LAT = Lot Acceptance Test.

For further information on LAT process flows see below.

[www.siliconsupplies.com/quality/bare-die-lot-qualification](http://www.siliconsupplies.com/quality/bare-die-lot-qualification)

## Supply Formats:

- Default – Die in Waffle Pack (400 per tray capacity)
- Sawn Wafer on Tape – By specific request
- Unsawn Wafer – By specific request
- With additional electrical selection – By specific request

## Mechanical Specification

Die Size (Unsawn)	965 x 965 37.99 x 37.99	$\mu\text{m}$ mils
Anode Pad Size	851 x 851 33.5 x 33.5	$\mu\text{m}$ mils
Die Thickness	250 ( $\pm 20$ ) 9.84 ( $\pm 0.79$ )	$\mu\text{m}$ mils
Top Metal Composition	Al $\geq 4\mu\text{m}$	
Back Metal Composition	NiTi/Ag (0.2/0.8 $\mu\text{m}$ )	





# 200 Watt, Uni-Directional TVS Diode

Rev 1.0

02/12/24

## Absolute Maximum Ratings $T_J = 25^\circ\text{C}$ unless otherwise stated

PARAMETER	SYMBOL	VALUE	UNIT
Peak power dissipation 10/1000 $\mu\text{s}$ waveform <sup>1</sup>	$P_{PP}$	200	W
Peak forward surge current, 8.3ms single half sine-wave <sup>2</sup>	$I_{FSM}$	20	A
ESD IEC61000-4-2 (Air) <sup>3</sup>	$V_{ESD}$	$\pm 30\text{V}$	kV
ESD IEC61000-4-2 (Contact) <sup>3</sup>			
Operating Temperature Range	$T_J$	-55 to +150	$^\circ\text{C}$
Storage Temperature Range	$T_S$	-65 to +200	$^\circ\text{C}$

1. Performance at die level dependent on assembly method and substrate choice. 2. Measured on 8.3 ms single half sine-wave or equivalent square wave, duty cycle = 4 pulses per minute maximum. 3. Tested in SOD-123FL package.

## Electrical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise stated

DEVICE <sup>4</sup>	REVERSE STAND-OFF VOLTAGE	BREAKDOWN VOLTAGE @ $I_T$		TEST CURRENT	MAX CLAMPING VOLTAGE $V_C @ I_{PP}$	PEAK PULSE CURRENT	REVERSE LEAKAGE $I_R @ V_{RRM}$
	$V_{RRM}$	$V_{BR(MIN)}$ (V)	$V_{BR(MAX)}$ (V)	$I_T$	$V_C$	$I_{PP}$	$I_R$
	V	V	V	mA	V	A	$\mu\text{A}$
SSL3.3A	3.3	5.23	5.97	10	8.0	23.5	30
SSL5.0A	5	6.43	6.97	10	9.2	21.7	4
SSL6.0A	6	6.70	7.34	10	10.3	19.4	1
SSL6.5A	6.5	7.25	7.95	10	11.2	17.9	1
SSL7.0A	7	7.81	8.57	10	12.0	16.7	1
SSL7.5A	7.5	8.36	9.18	1	12.9	15.5	1
SSL8.0A	8	8.92	9.80	1	13.6	14.7	1
SSL8.5A	8.5	9.47	10.37	1	14.4	13.9	1
SSL9.0A	9	10.03	11.07	1	15.4	13.0	0.25
SSL10A	10	11.13	12.27	1	17.0	11.8	0.25
SSL11A	11	12.23	13.47	1	18.2	11.0	0.25
SSL12A	12	13.33	14.67	1	19.9	10.1	0.25
SSL13A	13	14.43	15.87	1	21.5	9.3	0.08
SSL14A	14	15.63	17.17	1	23.2	8.6	0.08
SSL15A	15	16.73	18.29	1	24.4	8.2	0.08
SSL16A	16	17.83	19.67	1	26.0	7.7	0.08
SSL17A	17	18.93	20.87	1	27.6	7.2	0.08
SSL18A	18	20.03	22.07	1	29.2	6.8	0.08
SSL20A	20	22.23	24.47	1	32.4	6.2	0.08
SSL22A	22	24.43	26.87	1	35.5	5.6	0.08





# 200 Watt, Uni-Directional TVS Diode

Rev 1.0  
02/12/24

## Electrical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise stated

DEVICE <sup>4</sup>	REVERSE STAND-OFF VOLTAGE	BREAKDOWN VOLTAGE @ $I_T$		TEST CURRENT	MAX CLAMPING VOLTAGE $V_C @ I_{PP}$	PEAK PULSE CURRENT	REVERSE LEAKAGE $I_R @ V_{RRM}$
	$V_{RRM}$	$V_{BR(MIN)}$ (V)	$V_{BR(MAX)}$ (V)	$I_T$	$V_C$	$I_{PP}$	$I_R$
	V	V	V	mA	V	A	$\mu\text{A}$
SSL24A	24	26.73	29.47	1	38.9	5.1	0.8
SSL26A	26	28.93	31.87	1	42.1	4.8	0.8
SSL28A	28	31.13	34.37	1	45.4	4.4	0.8
SSL30A	30	33.33	36.77	1	48.4	4.1	0.8
SSL33A	33	36.73	40.57	1	53.3	3.8	0.8
SSL36A	36	40.03	44.17	1	58.1	3.4	0.8
SSL40A	40	44.40	49.10	1	64.5	3.1	0.8

4. Suffix "A" denotes 5% tolerance of  $V_{BR}$

**DISCLAIMER:** The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Silicon Supplies Ltd hereby disclaims any and all warranties and liabilities of any kind.

**LIFE SUPPORT POLICY:** Silicon Supplies Ltd components may be used in life support devices or systems only with the express written approval of Silicon Supplies Ltd, if a failure of such components can reasonably be expected to cause the failure of that life support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

