



60V 20A Schottky Diode - SiS170S060A

Silicon Schottky Rectifier in bare die form

Version 1.0
06/04/18

Applications

- Switching Power Supply
- Converters
- Free Wheeling Diodes

Features

- Ultra Low Reverse Current
- Soft recovery low & high temperature
- Low forward Voltage drop

Electrical Characteristics


Symbol	Parameter	Conditions	Typ	Max	Unit
V_R	Reverse Voltage	-	-	60	V
I_R	Reverse Current	$V_R = 60V, T_J = 25^\circ C$	-	3.00	mA
		$^1V_R = 60V, T_J = 125^\circ C$	-	200.0	mA
V_F	Forward Voltage	$I_F = 20A @ 25^\circ C$	-	0.65	V
T_J	Junction Temperature	-	-	150	$^\circ C$

Note 1: Not production tested at wafer level, tested in package

Mechanical Data

Die Attach Method	Front Metal Composition			Back Metal Composition		
Wire Bondable Top Solderable Back	-	Al (1% Si) 25kÅ	-	Ti	Ni	Ag 30kÅ

Die Drawing - Dimensions in Inches(mm)



DISCLAIMER: The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Silicon Supplies Ltd hereby disclaims any and all warranties and liabilities of any kind.

LIFE SUPPORT POLICY: Silicon Supplies Ltd components may be used in life support devices or systems only with the express written approval of Silicon Supplies Ltd, if a failure of such components can reasonably be expected to cause the failure of that life support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

