



Linear Voltage Regulator – SiS293033

Positive Fixed 3.3V 0.3A Ultra-Low Dropout Voltage Regulator in bare die form

Rev 1.0
29/04/24

Description

The SiS293033 low-noise, low dropout, high precision linear regulator operates with up to 12V input and provides 300mA output current. Typical output noise is 44µV_{RMS} with dropout voltage 270mV at 150mA load. The SiS293033 is highly accurate over temperature and exhibits excellent load and line transient response. Ruggedized features include internal output current limiting; short-circuit protection and thermal overload protection. Very small die size enables high integration.

Features:

- Low Temperature Coefficient: ±100ppm/°C
- Low Dropout: 270mV at 150mA
- ± 3% Voltage Accuracy at 300mA load
- Excellent Line Regulation: 0.05%/V
- Low Noise (10Hz to 100kHz): 44µV_{RMS}
- High PSRR: 60dB Range to 10kHz
- Input Voltage up to 12V (absolute max 14V)
- Low Quiescent Current: 8µA.

Ordering Information

The following part suffixes apply:


- No suffix - MIL-STD-883 /2010B Visual Inspection
- “H” - MIL-STD-883 /2010B Visual Inspection + MIL-PRF-38534 Class H LAT
- “K” - MIL-STD-883 /2010A Visual Inspection (Space) + MIL-PRF-38534 Class K LAT

LAT = Lot Acceptance Test.

For further information on LAT process flows see below.

www.siliconsupplies.com/quality/bare-die-lot-qualification

Die Dimensions in µm (mils)



Supply Formats:

- Default – Die in Waffle Pack (400 per tray capacity)
- Sawn Wafer on Tape – On request
- Unsawn Wafer – On request
- Tape & Reel – On request
- In Metal or Ceramic package – On request

Mechanical Specification

Die Size (Including Scribe)	840 x 680 33.07 x 26.77	µm mils
Minimum Bond Pad Size	70 x 70 2.75 x 2.75	µm mils
Die Thickness	350 (±20) 13.78 (±0.79)	µm mils
Top Metal Composition	Al 99.5% Cu 0.5%2µm	
Back Metal Composition	Si	






Linear Voltage Regulator – SiS293033

Rev 1.0
29/04/24


Pad Layout and Functions



PAD	FUNCTION	COORDINATES (µm)		DESCRIPTION
		X	Y	
1	V _{OUT}	75	545	Regulator Output. Requires 1µF low-ESR capacitor to GND for stable operation.
2	NC	75	346.36	Not Connected
3	NC	705.005	168.265	Not Connected
4	GND	705.005	268.27	Ground pin.
5	V _{IN}	705.005	544.995	Supply Input. Connect to power source (4.3V to 12V). Bypass with 1µF capacitor to GND.

CONNECT CHIP BACK TO V_{IN}

Typical Application



* C1 Input capacitor is recommended for all applications

** C2 is recommended for stability. 1µF Tantalum capacitor or 6.8µF ceramic capacitor is recommended.





Linear Voltage Regulator – SiS293033

Rev 1.0

29/04/24

Absolute Maximum Ratings¹

PARAMETER	SYMBOL	VALUE	UNIT
Supply Voltage	V _{IN}	14V	V
Power Dissipation ²	P _D	Internally Limited	
Operating Junction Temperature ³	T _J	-40 to 125	°C
Storage Temperature	T _{STG}	-65 to 150	°C
Thermal Resistance (Assembled in SOT-89-3)	R _{θJA}	93.4	°C/W
ESD Capability(HBM)	V _{ESD}	2	kV

Recommended Operating Conditions

PARAMETER	SYMBOL	MIN	MAX	UNIT
Input Voltage	V _{IN}	4.3	12	V
Output Current	I _{OUT}	10	300	mA
Operating Junction Temperature Range ³	T _J	-40 to 125		°C

DC Electrical Characteristics C_{IN} C_{OUT} = 1μF, T_J = 25°C (unless noted otherwise)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Output Voltage	V _{OUT}	V _{IN} = 4.3V, 1mA ≤ I _{OUT} ≤ 10mA	3.234	3.3	3.366	V
Line Regulation ⁴	ΔV _{OUT}	I _{OUT} = 10mA, 4V ≤ V _{IN} ≤ 6V	-	0.05	0.2	% / V _{OUT}
Load Regulation ⁴	ΔV _{OUT}	V _{IN} = 4.3V, 1mA ≤ I _{OUT} ≤ 300mA	-	60	-	mV
Output Voltage Accuracy		I _{OUT} = 300mA	-3	-	+3	%
Dropout Voltage	V _{DO}	I _{OUT} = 150mA	-	270	-	mV
Supply Current	I _S	V _{IN} = 4.3V, V _{OUT} Floating	-	8	15	μA
Output Voltage Noise	V _n	BW = 10Hz~100kHz	-	44	-	μV _{RMS}
	ΔV _{OUT} / ΔT.V _{OUT}	I _{OUT} = 10mA	-	±100	-	ppm/°C
Power Supply Rejection Ratio	PSRR	f = 100Hz Ripple = 0.5Vp-p, V _{IN} = 4.3V	-	60	-	dB
Maximum Output Current	I _{LIMIT}	V _{IN} - V _{OUT} = 1V	-	-	340	mA
Thermal Shutdown Threshold	T _{SHDN}		-	155	-	°C
Thermal Shutdown Hysteresis	ΔT _{SHDN}		-	25	-	°C

1. Operation above absolute maximum rating may cause device failure. Operation at the absolute maximum ratings, for extended periods, may reduce device reliability. 2. Maximum allowable power dissipation of any T_A (ambient temperature) is P_{DMAX} = (T_{JMAX} - T_A) / θ_{JA}. Exceeding the maximum allowable power dissipation will result in excessive die temperature and the regulator will go into thermal shutdown 3. This IC includes over temperature protection to protect the device during momentary overload conditions. Junction temperature will exceed 125°C when over temperature protection is active. Continuous operation above the specified maximum operating junction temperature may impair device reliability. 4. Regulation is measured at a constant junction temperature, using pulse testing with a low duty cycle.





Linear Voltage Regulator – SiS293033

Rev 1.0
29/04/24

Typical Electrical Characteristics $C_{IN} C_{OUT} = 1\mu F$, $T_J = 25^\circ C$ (unless noted otherwise)




Figure 1 – Quiescent Current VS Input Voltage




Figure 2 – Dropout Voltage VS Output Current




Figure 3 – PSRR VS Frequency

DISCLAIMER: The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Silicon Supplies Ltd hereby disclaims any and all warranties and liabilities of any kind.

LIFE SUPPORT POLICY: Silicon Supplies Ltd components may be used in life support devices or systems only with the express written approval of Silicon Supplies Ltd, if a failure of such components can reasonably be expected to cause the failure of that life support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

